

TROMB

All in one.

NEW DC Tromb Turbo

www.dustcontrol.us



Dustcontrol



Technical Data

DC Tromb Turbo – Direct start

HxWxD [mm/in]	1390x600x840/55x23x33
Weight [kg/lb]	A) Container 88/194 C) Bag 84/185 L) Longopac 86/190
Collection container [l/gal]	a) 40/10.6 c) 20/5.3 L) Longopac
Flow max, fan, US/CAN [m³/h/cfm]	315/186
Negative pressure, max, EU [kPa/inwg]	28/112
Power [hp]	4
Sound level [dB(A)]	72

Supplied with (Part No) 3-phase

Suction hose set, 7 m /23 ft, 5 m /16 ft (Ø50 mm /2") and 2 m /6.5 ft (Ø38 mm /1.5"), (2126)
 Floor nozzle B450 mm (7236)
 Suction pipe (Ø38 mm /1.5") (7257)
 Connecting sleeve (2114)
 Coupling socket (2107)
 Fine filter, polyester (44017)
 HEPA H13-filter (44016)

- 173502** A 4hp 460V /60Hz, US
- 173102** C 4hp 460V /60Hz, US
- 173302** L 4hp 460V /60Hz, US

DC Tromb Turbo – EX

HxWxD [mm/in]	1390x600x840/55x24x33
Weight [kg/lb]	A) Container 88/194
Collection container [l/gal]	40/10.6
Flow max, fan, US/CAN [m³/h/cfm]	315/186
Negative pressure, max, EU [kPa/inwg]	28/112
Power [hp]	4
Sound level [dB(A)]	72

Supplied with (Part No) 3-phase IP65

Suction hose Ø38/50 (2027 (2m), 2028 (5 m))
 Floor nozzle (7236E)
 Suction pipe (Ø38 mm /1.5") (7257)
 Antistatic Fine filter, polyester (44017-1)
 HEPA H13-filter (44016)
 Plastic bag (5 pcs) (42384)

173702 A 4hp 460V /60Hz, US/CAN



H-classified for a reason.

The filter systems in all mobile Dustcontrol dust extractors are built to comply with the EN 60335-2-69, Annex AA, H-class.



QR Code for more info.

Scan this QR code and get more info about the DC Tromb Turbo models; videos, guidelines and much more.



Healthy Business since 1972.

Dustcontrol AB is a Swedish company with a team originating from more than 20 countries! We have 5 subsidiaries and 40 resellers worldwide. Healthy People – Healthy Business.

TROMB

Quality, Containment & Performance – All in one.




DC Tromb Turbo

- Powerful three-phase turbo motor.
- Easier filter change procedure.
- Tall cyclone & sturdy chassis.
- Quick coupling for filter change.
- Equipped with a Hepa H13 and a washable polyester filter.
- Semi automatic filter cleaning.

The DC Tromb Turbo

We have launched two powerful dust free solutions

The DC Tromb Turbo with direct start is a medium sized dust extractor that expands the Tromb family. It is equipped with a powerful three-phase turbo motor which is suitable for heavy cleaning (38 mm/1.5" accessories) and is delivered with 7 m hose. Suitable for source extraction from medium sized power tools such as grinders, jack hammers and saws. Thanks to the tall cyclone, large filters and powerful motor package, it can handle large amounts of debris. You have three options for a collection container: A (steel container), C (plastic bag) or L (Longopac).

 **The DC Tromb Turbo EX for ATEX zone 22.** This is a medium sized dust extractor that expands the Tromb Family. It is equipped with a powerful three-phase turbo motor suitable for heavy cleaning (38 mm/1.5" accessories) and is delivered with 7 m hose. It is certified to IP65 standard, ATEX zone 22 (conductive dust). Our DC Tromb Turbo Ex is equipped with a steel collection container.



DC Tromb Turbo
with **Direct start**



DC Tromb Turbo
EX for ATEX zone 22



Select from one of three collection containers



Plastic Bag



Steel Container



Longopac



www.dustcontrol.us